

Leak Test Connector Selection Guide





Introduction to FasTest

Leak Testing Today ...

Since 1985, *FasTest* advanced engineering creates connecting solutions that are easier, safer and more reliable while dramatically lowering your operating costs. With *FasTest*, you can expect increased operational throughput and a fast return on your investment.

Tens of thousands of satisfied customers have made the switch from their inadequate, unproductive leak test connectors to our engineered testing and filling solutions.

FasTest products are used by every major automotive manufacturer, top appliance companies, medical device manufacturers, aerospace, power generation, plus hundreds of other industries throughout the world.

Our complete selection of engineers products combined with extensive experience and expertise allows us to help you specify the right connector for your application. Small differences can diminish the suitability of a connector for your application. At *FasTest* we can modify standard products to fit your specific needs or engineer a total custom test system.

Helpful Hint ...

Cumbersome leak testing methods using jury-rigged adapters, fittings and test jigs is time-consuming, unreliable and may be unsafe to your workers.

FasTest connecting tools are available in many configurations - each precision engineered to perform specific pressure and vacuum test and built to fit your testing and process requirements.

FasTest offers extensive expertise to help you arrive at the optimum solution for your application and workflow. With over 50 patents and as the acknowledged expert in the field, chances are we've solved an application like yours, no matter how challenging.

Do as thousands of others have done. Make the switch from older inadequate or homemade jury-rigged adapters to *FasTest* engineered testing and filling solutions.

Seal Materials ...

Selecting the right seal material is critical to the reliability of the connector and the amount of maintenance required. *FasTest* manufactured seals exhibit superior wear resistance and maintain its sealing properties.

FasTest offers neoprene, urethane, Viton, EPDM, Buna-N, and FDA white neoprene. Our seals are manufactured via *FasTest* proprietary process which is why our seals are more durable, longer lasting and create a better leak tight connection.


















TwistMate®

FasTest's complete product family of *TwistMate* connectors, plugs and caps provide fast leak tight threaded connections for testing, filling, flushing, plugging, calibrating or venting applications. Simply spin our connectors finger-tight onto thread until face seal contacts test piece.

TwistMates seal automatically when the system is pressurized. Air, gas or hydraulic pressure in the system provides a sealing force that presses the main seal against the face of the threads. This automatic internal piston action maintains the seal with minimum pressure.



Features:

- Pressure assisted grip and seal technology
- Available in NPT, BSPP, BSPT, SAE, Metric and special thread profiles
- Repair kits available for extended connector service life
- Finger-tight pneumatic or hydraulic connections from vacuum to 10,000 psi
- Stainless steel construction for corrosion resistance
- Reduce production losses, retest time, scrap and test damage repair costs

Applications:

- · Water dunk leak testing
- · Leak, flow, flushing or washing
- Cylinders, manifolds, valves, pumps filters and assemblies
- Bubble, pressure decay and mass spectrometer testing
- Heat exchangers, brake and steering system assemblies
- Capping and plugging pipes, fittings or hose ends

| | Contents | Page(s) |
|------------------|-------------|---------|
| | Tech Info | D1-D3 |
| | NPT | D4 |
| ads | SAE | D6 |
| Thre | BSPP | D7 |
| Internal Threads | BSPT | D8 |
| Inte | Plugs - All | D9 |
| | Metric | D10 |
| S | NPT | D11 |
| Iread | SAE | D13 |
| External Threads | BSPP | D14 |
| xtern | BSPT | D14 |
| ίΩ. | Caps - All | D15 |




The TwistMate Technology

The **TwistMate** family of products use an innovative "*twist to connect*" and pressure assisted grip and seal technology to deliver a fast, safe and repeatable high pressure or vacuum testing connection in threaded ports

or tubing. This sealing technique creates an improved seal as pressures increase and eliminates the traditional sealing methods using tape and wrenches that can damage internal or external threads.

"MIT Series" Connectors for Internal / Female Threads






- 1. Spin *TwistMate* into the threaded port until the seal makes contact.
- 2. Introduce the media and pressure. The external sleeve automatically moves toward the test piece enhancing the seal squeeze. Vacuum applications will require finger tightening.

"MET Series" Connectors for External / Male Threads





- 1. Spin TwistMate on to the threaded port until the seal makes contact.
- 2. Introduce the media and pressure. The internal piston automatically moves toward the test piece enhancing the seal squeeze. Vacuum applications will require finger tightening.

FasTest

TwistMate Part Number Key

| | | | | - 1 | | | ~ 4 | | | | v | | | | | | | |
|---------------------------------|--------------|-----------------|----|----------------|-----|---|-----|---|----|-------|--------------|----------|---------|-----------|--------------|----------|-------------------|--------------|
| | | | MI | | H | - | 04 | 2 | 4 | 1 | Х | | - | | | | | |
| Model | | | | | L | | | | | | | | | | | | S | pecial Optic |
| MET - Mechan | | | | | L | | | | | | | | | | k = None | | | |
| MIT - Mechanie | cal Internal | Thread | | | L | | | | | | | | | PT = | For thin wa | alled pi | pe threa | ads |
| Optional Confi | igurations | | | | | | | | | | | | | | | | | Seal Mate |
| Blank = Standa | rd | | | | | | | | | | | E | Blank : | = Stand | ard seal (se | e indiv | idual pa | art numbers) |
| C = For curved | surfaces | | | | | | | | | | | | 3 = Bu | | | | | |
| H = High press | ure | | | | | | | | | | | | E = EF | | | | | |
| Connector | NPT | | | | | | | | | | | | | oprene | | | | |
| Size | BSPP/T | SAE | | Metr | ic | | | | | | | | 5 = Sil | ethane | | | | |
| 02 | 1 /0 | | | | - | | | | | | | - | / = Vit | | | | | |
| 02 | | 3/8-24 | | | | | | | | | | • | | 011 | | | | |
| 04 | | 7/16-20 | | | | | | | | | | | | | | Con | nector | Configurat |
| 05 | | 1/2-20 | | | | | | | | | В | lank | = Swi | vel style | e | | | |
| 06 | | 9/16-18 or 5/8- | 18 | | | | | | | | | | | vivel cor | | | | |
| 08 | 1/2 | 3/4-16 | | | | | | | | | | | | | | | | |
| 10 | | 7/8-14 | I | V10> | x 1 | | | | | Т | ərmir | natio | on Typ | e | | | | |
| 12 | | 1 1/16-12 | 1 | V12 > | x 1 | | | | | 1 | = Fe | male | NPT | | | | | |
| 14 | | 1 3/16-12 | - | V14 > | | | | | | 2 | = Ma | le N | PT | | | | | |
| 16 | | 1 5/16-12 | | V16 > | | | | | | 3 | = Fe | male | SAE | , O-ring | Boss | | | |
| 18 | | | | 118 x | | | | | | 4 | = Ma | le S | AE O- | ring Bo | SS | | | |
| 20 | | 1 5/8-12 | | 120 x 122 x | | | | | | | | | BSP | | | | | |
| 22 | | 1 7/8-12 | IV | 122 X | 1.5 | | | | | | | | le BSI | PT | | | | |
| 32 | | | | | | | | | | | = Ma | | | | | | | |
| 40 | | | | | | | | | | | | | BSPT | - | | | | |
| 48 | | | | | | | | | | | = Fe = Ma | | e metri | IC | | | | |
| 64 | 4 | | | | | | | | | | | | | 37º flar | ò | | | |
| | | | | | | | | | | | | | | ° flare | C | | | |
| Connector Typ |)e | | | | | | | | | | | | | 45° flar | e | | | |
| 1 = Female NP | Т | | | | | | | | - | | | <u>.</u> | _ | | NPT | | | |
| 2 = Male NPT | | | | | | | | | Ie | rmin | ation | SIZ | e | | NPI | | SAE | |
| 3 = Female SA | | DSS | | | | | | | | | | | | | 1/8 | | | |
| 4 = Male SAE (| 0 | | | | | | | | | | | | | | 1/4 | | 7/16-2 | |
| 5 = Female BS | | | | | | | | | | | | | | | 3/8 | | 9/16-1 | |
| 5T = Female BS 6 = Male BSPP | | | | | | | | | | | | | | | 1/2 | | 3/4-16 | - |
| 6T = Male BSPP | | | | | | | | | | | | | | | | | 7/8-14 1 1/16- | |
| 7 = Female me | | | | | | | | | | | | | | | 1 | | | 14 |
| 8 = Male metric | | | | | | | | | | | | | | | 1-1/4 | | | |
| 9 = Female SA | | | | | | | | | | | | | | | 1-1/2 | | | |
| 0 = Male SAE 3 | 37° flare | | | | | | | | | = Ca | | | | | | | | |
| A = Female SA | - 4-0 flama | | | | | | | | - | = Plu | | | | | | | | |


Notes:

Part Number Keys are to assist in IDENTIFICATION ONLY.

Verify new part numbers with factory; some configurations are not possible.




Connectors for Internal (Female) NPT Threads



NPT - Swivel Style (per SAE J476 or ANSI B1.20)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-022021 | 1/8" NPT | 0.82" | 1.68" | 1/8" NPT | 5000 | | | MITR-020 | S1109-U70 |
| MIT-042041 | 1/4" NPT | 1.00" | 1.88" | 1/4" NPT | 5000 | | l leath an at | MITR-040 | S1111-U70 |
| MIT-062061 | 3/8" NPT | 1.18" | 2.09" | 3/8" NPT | | Swivel Ure | | MITR-060 | S1113-U70 |
| MIT-082081 | 1/2" NPT | 1.36" | 2.57" | 1/2" NPT | 4000 | Swiver | Urethane* | MITR-080 | S1209-U70 |
| MIT-122121 | 3/4" NPT | 1.68" | 2.73" | 3/4" NPT | 4000 | 000 | | MITR-12 | S1109-U70 |
| MIT-162161 | 1" NPT | 2.00" | 3.27" | 1" NPT | | | | MITR-16 | S1010-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-022021E = EPDM




NPT - Non-Swivel Style (per SAE J476 or ANSI B1.20)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|------------|-------|-------|------------|---------------|-----------------------|------------------|---------------|---------------------------|
| MIT-022021X | 1/8" NPT | 0.82" | 1.24" | 1/8" NPT | 5000 | | | MITR-02 | S1109-U70 |
| MIT-042041X | 1/4" NPT | 1.00" | 1.41" | 1/4" NPT | 5000 | | | MITR-04 | S1111-U70 |
| MIT-062061X | 3/8" NPT | 1.18" | 1.48" | 3/8" NPT | | | | MITR-06 | S1113-U70 |
| MIT-082081X | 1/2" NPT | 1.36" | 1.85" | 1/2" NPT | | | | MITR-08 | S1209-U70 |
| MIT-122121X | 3/4" NPT | 1.68" | 1.94" | 3/4" NPT | 4000 | | | MITR-12 | S1213-U70 |
| MIT-162161X | 1" NPT | 2.00" | 2.07" | 1" NPT | | Non Swivel Urethan | l Irothono* | MITR-16 | S1216-U70 |
| MIT-202201X | 1-1/4" NPT | 2.38" | 2.13" | 1-1/4" NPT | | | Orethane | MITR-20 | S1222-U70 |
| MIT-242241X | 1-1/2" NPT | 2.74" | 2.40" | 1-1/2" NPT | 3000 | | | MITR-24 | S1327-U70 |
| MIT-322161X | 2" NPT | 3.47" | 2.68" | 1" NPT | 2500 | | | MITR-32 | S1331-U70 |
| MIT-402161X | 2-1/2" NPT | 3.97" | 3.42" | 1" NPT | 1500 | | | MITR-40 | S1335-U70 |
| MIT-482161X | 3" NPT | 4.73" | 3.68" | 1" NPT | 1500 | | | MITR-48 | S1340-U70 |
| MIT-642161X | 4" NPT | 5.73" | 3.68" | 1" NPT | 1000 | | | MITR-64 | S1348-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-022021XV = FKM (Viton)



Connectors for Internal (Female) NPT Threads on Curved Surfaces




NPT - Non-Swivel Style for Curved Surfaces (per SAE J476 or ANSI B1.20)


| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|--------------|----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MITC-022021X | 1/8" NPT | 0.82" | 1.24" | 1/8" NPT | 5000 | Non | l Irothono* | MITR-02 | S1010-U70 |
| MITC-042041X | 1/4" NPT | 1.00" | 1.41" | 1/4" NPT | 5000 | Swivel | Urethane* | MITR-04 | S1013-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MITC-042041XB = Buna N

The *TwistMate* MITC Series connectors are designed to seal the port on the round of a surface better and with less effort. The unique chamfer seal design provides positive sealing with no thread sealants or wrench tightening.

| Part Number | Max. at Dim A | Bore Ø. Dim B | Chamfer Ø Dim C | Min. Body Ø Dim D |
|--------------|------------------|------------------|--------------------|----------------------|
| MITC-022021X | 0.030" | 0.500" | 1.24" | 0.880" |
| MITC-042041X | 0.045" | 0.625" | 1.41" | 1.200" |





NPT - Non-Swivel Style for High Pressure (per SAE J476 or ANSI B1.20)


| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|--------------|----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MITH-022021X | 1/8" NPT | 0.82" | 1.24" | 1/8" NPT | | | | MITR-02 | S1109-U70 |
| MITH-042041X | 1/4" NPT | 1.00" | 1.41" | 1/4" NPT | 10,000 | | | MITR-04 | S1111-U70 |
| MITH-062061X | 3/8" NPT | 1.18" | 1.48" | 3/8" NPT |] | Non | Urethane* | MITR-06 | S1113-U70 |
| MITH-082081X | 1/2" NPT | 1.36" | 1.85" | 1/2" NPT | 8000 | Swivel | Orethane | MITR-08 | S1209-U70 |
| MITH-122121X | 3/4" NPT | 1.68" | 1.94" | 3/4" NPT | 7500 | | | MITR-12 | S1213-U70 |
| MITH-162161X | 1" NPT | 2.00" | 2.07" | 1" NPT | 6500 | | | MITR-16 | S1216-U70 |

*Optional seal materials is EPDM - Example: MITH-042041XE = EPDM

FwistMate




Connectors for Internal (Female) SAE O-Ring Boss Threads



SAE - Non-Swivel Style (per SAE J1926 or ISO 11926)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|-----------------|-------|-------|------------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-034021X | -3 (3/8-24) | 0.82" | 1.29" | 1/8" NPT | | | | MITR-02 | S1109-U70 |
| MIT-044021X | -4 (7/16-20) | 0.82" | 1.29" | 1/8" NPT | 5000 | | | WITR-02 | S1109-U70 |
| MIT-054041X | -5 (1/2-20) | 1.00" | 1.41" | 1/4" NPT | 5000 | | | MITR-04 | S1111-U70 |
| MIT-064041X | -6 (9/16-18) | 1.00" | 1.41" | 1/4" NPT | | | | WII I K-04 | S1111-U70 |
| MIT-084081X | -8 (3/4-16) | 1.36" | 1.85" | 1/2" NPT | | Non | Urethane* | MITR-08 | S1209-U70 |
| MIT-104081X | -10 (7/8-14) | 1.36" | 1.85" | 1/2" NPT | | Swivel | Orethane | WII I K-UO | S1209-U70 |
| MIT-124121X | -12 (1 1/16-12) | 1.68" | 1.94" | 3/4" NPT | 4000 | | | MITR-12 | S1213-U70 |
| MIT-144161X | -14 (1 3/16-12) | 2.00" | 2.13" | 1" NPT | 4000 | | | MITR-16 | S1216-U70 |
| MIT-164161X | -16 (1 5/16-12) | 2.00" | 2.13" | 1" NPT | | | | IVII I R-16 | S1217-U70 |
| MIT-204201X | -20 (1 5/8-12) | 2.38" | 2.13" | 1-1/4" NPT | | | | MITR-20 | S1222-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-044021X V = FKM (Viton)



SAE - Non-Swivel Style for High Pressure (per SAE J1926 or ISO 11926)


| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|-----------------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MITH-044021X | -4 (7/16-20) | 0.82" | 1.29" | 1/8" NPT | 10,000 | | | MITR-02 | S1109-U70 |
| MITH-064041X | -6 (9/16-18) | 1.00" | 1.41" | 1/4" NPT | 10,000 | | | MITR-04 | S1111-U70 |
| MITH-084081X | -8 (3/4-16) | 1.36" | 1.85" | 1/2" NPT | 8000 | | | | MITR-08 |
| MITH-104081X | -10 (7/8-14) | 1.36" | 1.85" | 1/2" NPT | 7500 | Non Swivel | Urethane* | IVII I R-00 | S1209-U70 |
| MITH-124121X | -12 (1 1/16-12) | 1.68" | 1.94" | 3/4" NPT | 7500 | | owiver | MITR-12 | S1213-U70 |
| MITH-144161X | -14 (1 3/16-12) | 2.00" | 2.13" | 1" NPT | 7000 | 7000 | | MITR-16 | S1216-U70 |
| MITH-164161X | -16 (1 5/16-12) | 2.00" | 2.13" | 1" NPT | /000 | | | | S1217-U70 |

*Optional seal materials is EPDM - Example: MITH-064041XE = EPDM

TwistMate[®] - Threaded Connectors



Connectors for Internal (Female) BSPP Threads




BSPP - Swivel Style (per ISO 228 or BS 2779)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|-------------|-----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-026021 | 1/8" BSPP | 0.82" | 1.24" | 1/8" NPT | 5000 | | | MITR-020 | S1109-U70 |
| MIT-046041 | 1/4" BSPP | 1.00" | 1.41" | 1/4" NPT | 5000 | Swivel | Urethane* | MITR-040 | S1111-U70 |
| MIT-066061 | 3/8" BSPP | 1.18" | 1.48" | 3/8" NPT | 4000 | | | MITR-060 | S1113-U70 |
| MIT-086081 | 1/2" BSPP | 1.36" | 1.85" | 1/2" NPT | 4000 | | | MITR-080 | S1209-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-046041XB = Buna N






BSPP - Non-Swivel Style (per ISO 228 or BS 2779)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|-------------|-----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-126121X | 3/4" BSPP | 1.68" | 1.94" | 3/4" NPT | 4000 | Non | l Irothana* | MITR-12 | S1213-U70 |
| MIT-166161X | 1" BSPP | 2.00" | 2.07" | 1" NPT | 4000 | Swivel | Urethane* | MITR-16 | S1216-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-126121XV = FKM (Viton)




Connectors for Internal (Female) BSPT Threads



BSPT - Swivel Style (per ISO 7 or BS 21)

| | Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|---|----------------|-----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| | MIT-026T021 | 1/8" BSPT | 0.82" | 1.24" | 1/8" NPT | 5000 | | | MITR-020 | S1109-U70 |
| ĺ | MIT-046T041 | 1/4" BSPT | 1.00" | 1.41" | 1/4" NPT | 5000 | Curinteel | ivel Urethane* | MITR-040 | S1111-U70 |
| | MIT-066T061 | 3/8" BSPT | 1.18" | 1.48" | 3/8" NPT | 4000 | Swivel | | MITR-060 | S1113-U70 |
| | MIT-086T081 | 1/2" BSPT | 1.36" | 1.85" | 1/2" NPT | 4000 | | | MITR-080 | S1209-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-046T041XV = FKM (Viton)



BSPT - Non-Swivel Style (per ISO 7 or BS 21)


| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|-----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-126T121X | 3/4" BSPT | 1.68" | 1.94" | 3/4" NPT | 4000 | Non | l Irothono* | MITR-12 | S1213-U70 |
| MIT-166T161X | 1" BSPT | 2.00" | 2.07" | 1" NPT | 4000 | Swivel | Urethane* | MITR-16 | S1216-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-126T121E = EPDM



Plugs for Internal (Female) NPT, BSPP and BSPT Threads





NPT Threads (per SAE J476 or ANSI B1.20)

| Part Number | Dim A | Dim B | Dim C | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|-------------|----------|-------|-------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-022P | 1/8" NPT | 0.82" | 1.24" | 5000 | | | MITR-02 | S1109-U70 |
| MIT-042P | 1/4" NPT | 1.00" | 1.41" | 5000 | | | MITR-04 | S1111-U70 |
| MIT-062P | 3/8" NPT | 1.18" | 1.48" | | Dhur | l leath an a* | MITR-06 | S1113-U70 |
| MIT-082P | 1/2" NPT | 1.36" | 1.85" | 4000 | Plug | Urethane* | MITR-08 | S1209-U70 |
| MIT-122P | 3/4" NPT | 1.68" | 1.94" | 4000 | | | Consult | S1213-U70 |
| MIT-162P | 1" NPT | 2.00" | 2.07" | | | | Factory | S1216-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-042P<u>V</u> = FKM (Viton)

BSPP Threads (per ISO 228 or BS 2779)

| Part Number | Dim A | Dim B | Dim C | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|-------------|-----------|-------|-------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-026P | 1/8" BSPP | 0.82" | 1.24" | 5000 | | | MITR-02 | S1109-U70 |
| MIT-046P | 1/4" BSPP | 1.00" | 1.41" | 5000 | Dlug | Lirothono* | MITR-04 | S1111-U70 |
| MIT-066P | 3/8" BSPP | 1.18" | 1.48" | 4000 | Plug | Urethane* | MITR-06 | S1113-U70 |
| MIT-086P | 1/2" BSPP | 1.36" | 1.85" | 4000 | | | MITR-08 | S1209-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-046PE = EPDM

BSPT Threads (per ISO 7 or BS 21)

| Part Number | Dim A | Dim B | Dim C | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|-------------|-----------|-------|-------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-026TP | 1/8" BSPT | 0.82" | 1.24" | 5000 | Plug | | MITR-02 | S1109-U70 |
| MIT-046TP | 1/4" BSPT | 1.00" | 1.41" | 5000 | | Urethane* | MITR-04 | S1111-U70 |
| MIT-066TP | 3/8" BSPT | 1.18" | 1.48" | 4000 | | | MITR-06 | S1113-U70 |
| MIT-086TP | 1/2" BSPT | 1.36" | 1.85" | 4000 | | | MITR-08 | S1209-U70 |


*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-046PB = Buna N

TwistMate Internal Repair Kits

Swivel style repair kits contains 2 internal Buna N O-rings, 2 backup rings and 1 snap ring. Non-Swivel style repair kits contain 1 internal Buna N O-ring and 1 backup ring. Repair kits do not include main seal replacement. For additional kits consult factory.



Connectors for Internal (Female) ISO O-Ring Metric Threads



ISO O-Ring Metric - Non-Swivel Style (per ISO 6149 or SAE J2244)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|-----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MIT-108021X | M10 x 1.0 | 0.82" | 1.30" | 1/8" NPT | | | | MITR-02 | S1109-U70 |
| MIT-128041X | M12 x 1.5 | 1.00" | 1.42" | 1/4" NPT | 5000 | | | | S1110-U70 |
| MIT-148041X | M14 x 1.5 | 1.00" | 1.42" | 1/4" NPT | | Non | | MITR-04 | S1111-U70 |
| MIT-168061X | M16 x 1.5 | 1.18" | 1.56" | 3/8" NPT | | Swivel | Urethane* | MITR-06 | S1113-U70 |
| MIT-188061X | M18 x 1.5 | 1.18" | 1.56" | 3/8" NPT | 4000 | | | IVII I R-06 | S1114-U70 |
| MIT-228081X | M22 x 1.5 | 1.36" | 1.87" | 1/2" NPT | | | | MITR-08 | S1116-U70 |


*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-148041XV = FKM (Viton)

D

TwistMate® - Threaded Connectors




Connectors for External (Male) NPT Threads



NPT Threads (per SAE J476 or ANSI B1.20)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) | |
|-------------|------------|-------|-------|------------|---------------|------------------|------------------|---------------|---------------------------|-----------|
| MET-021022 | 1/8" NPT | 0.82" | 1.51" | 1/8" NPT | 5000 | | | METR-02 | S1105-U70 | |
| MET-041042 | 1/4" NPT | 0.94" | 1.74" | 1/4" NPT | 5000 | | | METR-04 | S1108-U70 | |
| MET-061062 | 3/8" NPT | 1.18" | 1.78" | 3/8" NPT | | 1 | | METR-06 | S1110-U70 | |
| MET-081082 | 1/2" NPT | 1.60" | 2.05" | 1/2" NPT | 4000 | Swivel | Urethane* | METR-08 | S1112-U70 | ate |
| MET-121122 | 3/4" NPT | 1.68" | 2.34" | 3/4" NPT | 4000 | | | METR-12 | S1115-U70 | stM |
| MET-161162 | 1" NPT | 2.00" | 2.74" | 1" NPT |] | | | METR-16 | S1212-U70 | TwistMate |
| MET-201202 | 1-1/4" NPT | 2.37" | 3.27" | 1-1/4" NPT | 2500 | | | METR-20 | S1217-U70 | |




NPT Threads (per SAE J476 or ANSI B1.20)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) | |
|-------------|------------|-------|-------|--------|---------------|------------------|------------------|---------------|---------------------------|--------|
| MET-241161 | 1-1/2" NPT | 2.37" | 3.27" | 1" NPT | 1000 | | | METR-24 | METB24 | |
| MET-321161 | 2" NPT | 3.00" | 2.53" | 1" NPT | 750 | Swiwal | Urethane* | | METR-32 | METB32 |
| MET-401161 | 2-1/2" NPT | 3.40" | 2.54" | 1" NPT | 500 | Swivel | | METR-40 | METB40 | |
| MET-481161 | 3" NPT | 4.25" | 2.61" | 1" NPT | 500 | | | METR-48 | METB48 | |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MET-041042E = EPDM




Connectors for External (Male) NPT Threads



NPT Threads for High Pressure (per SAE J476 or ANSI B1.20)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| METH-021022 | 1/8" NPT | 0.82" | 1.51" | 1/8" NPT | 10,000 | | | METR-02 | S1105-U70 |
| METH-041042 | 1/4" NPT | 0.94" | 1.74" | 1/4" NPT | 8000 | | | METR-04 | S1108-U70 |
| METH-061062 | 3/8" NPT | 1.18" | 1.78" | 3/8" NPT | 8000 | Swivel | Urethane* | METR-06 | S1110-U70 |
| METH-081082 | 1/2" NPT | 1.60" | 2.05" | 1/2" NPT | 6000 | Swiver | Ulethane | METR-08 | S1112-U70 |
| METH-121122 | 3/4" NPT | 1.68" | 2.34" | 3/4" NPT | 5500 | | | METR-12 | S1115-U70 |
| METH-161162 | 1" NPT | 2.00" | 2.74" | 1" NPT | 5000 | | | METR-16 | S1212-U70 |

*Optional seal materials is EPDM - Example: METH-041042E = EPDM



NPT Threads on Thin Walled Threaded Pipe (per SAE J476 or ANSI B1.20)


| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|------------|-------|-------|------------|---------------|------------------|------------------|---------------|---------------------------|
| MET-041042-PT | 1/4" NPT | 0.94" | 1.74" | 1/4" NPT | | | | METR-04 | METB-04PT |
| MET-061062-PT | 3/8" NPT | 1.18" | 1.78" | 3/8" NPT | | | | METR-06 | METB-06PT |
| MET-081082-PT | 1/2" NPT | 1.60" | 2.05" | 1/2" NPT | | 750 | Dune N | METR-08 | METB-08PT |
| MET-121122-PT | 3/4" NPT | 1.68" | 2.34" | 3/4" NPT | 750 | | Buna N | METR-12 | METB-12PT |
| MET-161162-PT | 1" NPT | 2.00" | 2.74" | 1" NPT | /50 | Swivel | | METR-16 | METB-16PT |
| MET-201202-PT | 1-1/4" NPT | 2.37" | 3.27" | 1-1/4" NPT | | Swiver | | METR-20 | METB-20PT |
| MET-241161* | 1-1/2" NPT | 2.37" | 3.27" | 1" NPT | | | | METR-24 | METB24 |
| MET-321161 | 2" NPT | 3.00" | 2.53" | 1" NPT | 500 | | Urothono | METR-32 | METB32 |
| MET-401161 | 2-1/2" NPT | 3.40" | 2.54" | 1" NPT | | 500 Urethane | Uremane | METR-40 | METB40 |
| MET-481161 | 3" NPT | 4.25" | 2.61" | 1" NPT | 500 | | | METR-48 | METB48 |

*Connector pressure rating reduced to 750 psi for thin wall threaded pipe applications.

FasTest

Connectors for External (Male) SAE Flare Threads






SAE - 37º Flare, "AN" Standard, Swivel Style for High Pressure (per SAE J514 or ISO 12151-5)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|-------------|-----------------|-------|-------|-----------------|---------------|------------------|------------------|---------------|---------------------------|
| METH-049040 | -4 (7/16-20) | 0.95" | 1.76" | -4 (7/16-20) | | | | METR-049 | S2070-0270B70 |
| METH-069060 | -6 (9/16-18) | 1.20" | 1.83" | -6 (9/16-18) |] | | | METR-06 | S1012-B70 |
| METH-089080 | -8 (3/4-16) | 1.38" | 2.00" | -8 (3/4-16) | 10,000 | Swivel | Buna N* | METR-08 | S1015-B70 |
| METH-109100 | -10 (7/8-14) | 1.51" | 2.35" | -10 (7/8-14) | | | | | S1016-B70 |
| METH-129120 | -12 (1 1/16-12) | 1.70" | 2.52" | -12 (1 1/16-12) | | | | METR-12 | S1018-B70 |

*Optional seal materials is EPDM - Example: METH-069060E = EPDM



For SAE 45° Flare (per SAE J512 or J513)


| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|-------------|---------------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MET-04A042B | -4 (7/16-20) | 0.95" | 1.76" | 1/4" NPT | 5000 | | Buna N** | METR-049 | S2060-0246B70 |
| MET-06A062N | -6 (5/8-18) | 1.20" | 1.83" | 3/8" NPT | 5000 | | | METR-06 | S1012-N70 |
| MET-08A082N | -8 (3/4-16) | 1.38" | 2.00" | 1/2" NPT | | Swivel | Neoprene* | METR-08 | S1014-N70 |
| MET-10A082N | -10 (7/8-14) | 1.51" | 2.35" | 1/2" NPT | 4000 | | | | S1015-N70 |
| MET-12A122N | -12 (1 16-14) | 1.70" | 2.52" | 3/4" NPT | | | | METR-12 | S1117-N70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MET-08A082NE = EPDM

**Optional seal materials are FKM (Viton) and EPDM - Example: MET-04A042B⊻ = FKM (Viton)




Connectors for External (Male) BSPP and BSPT Threads



BSPP - Swivel Style (per ISO 228 or BS 2779)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|-----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MET-025022 | 1/8" BSPP | 0.80" | 1.62" | 1/8" NPT | 5000 | | | METR-02 | S1105-U70 |
| MET-045042 | 1/4" BSPP | 0.93" | 1.63" | 1/4" NPT | 5000 | Swivel | Urethane* | METR-04 | S1108-U70 |
| MET-065062 | 3/8" BSPP | 1.20" | 1.31" | 3/8" NPT | 4000 | | | METR-06 | S1110-U70 |
| MET-085082 | 1/2" BSPP | 1.36" | 1.46" | 1/2" NPT | 4000 | | | METR-08 | S1112-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MET-045042B = Buna N




BSPT - Swivel Style (per ISO 7 or BS 21)

| Part Number | Dim A | Dim B | Dim C | Dim D | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) |
|----------------|-----------|-------|-------|----------|---------------|------------------|------------------|---------------|---------------------------|
| MET-025T022 | 1/8" BSPT | 0.80" | 1.62" | 1/8" NPT | 5000 | Swivel | Urethane* | METR-02 | S1105-U70 |
| MET-045T042 | 1/4" BSPT | 0.93" | 1.63" | 1/4" NPT | 5000 | | | METR-04 | S1108-U70 |
| MET-065T062 | 3/8" BSPT | 1.20" | 1.31" | 3/8" NPT | 4000 | | | METR-06 | S1110-U70 |
| MET-085T082 | 1/2" BSPT | 1.36" | 1.46" | 1/2" NPT | 4000 | | | METR-08 | S1112-U70 |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MET-045T042E = EPDM



Caps for External (Male) NPT, BSPP and BSPT Threads



Cap Style for NPT Threads (per SAE J476 or ANSI B1.20)

| Part Number | Dim A | Dim B | Dim C | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) | |
|-------------|----------|-------|-------|---------------|------------------|------------------|---------------|---------------------------|-----------|
| MET-021C | 1/8" NPT | 0.80" | 0.83" | 5000 4000 | | l lucih en e* | METR-02 | S1105-U70 | |
| MET-041C | 1/4" NPT | 0.93" | 0.88" | | | | METR-04 | S1108-U70 | |
| MET-061C | 3/8" NPT | 1.20" | 0.90" | | 4000 | Сар | Urethane* | METR-06 | S1110-U70 |
| MET-081C | 1/2" NPT | 1.36" | 0.97" | | 4000 | | METR-08 | S1112-U70 | |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MET-041CV = FKM (Viton)

Cap Style for BSPP Threads (per ISO 228 or BS 2779)

| Part Number | Dim A | Dim B | Dim C | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) | | | |
|-------------|-----------|-------|-------|---------------|------------------|------------------|---------------|---------------------------|------------|---------|-----------|
| MET-025C | 1/8" BSPP | 0.80" | 0.83" | 5000 4000 | 5000 | | METR-02 | S1105-U70 | | | |
| MET-045C | 1/4" BSPP | 0.93" | 0.88" | | | 5000 | 5000 | Con | Lirothono* | METR-04 | S1108-U70 |
| MET-065C | 3/8" BSPP | 1.20" | 0.90" | | | Сар | Urethane* | METR-06 | S1110-U70 | | |
| MET-085C | 1/2" BSPP | 1.36" | 0.97" | | | | METR-08 | S1112-U70 | | | |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MET-045CE = EPDM

Cap Style for BSPT Threads (per ISO 7 or BS 21)

| Part Number | Dim A | Dim B | Dim C | Rating PSI | Housing Style | Seal Material | Repair Kit | Main Seals Package (5) | | | |
|-------------|-----------|-------|-------|---------------|------------------|------------------|---------------|---------------------------|------------|---------|-----------|
| MET-025TC | 1/8" BSPT | 0.80" | 0.83" | 5000 | | | METR-02 | S1105-U70 | | | |
| MET-045TC | 1/4" BSPT | 0.93" | 0.88" | | | 5000 | 5000 | Can | Lirothono* | METR-04 | S1108-U70 |
| MET-065TC | 3/8" BSPT | 1.20" | 0.90" | | | Сар | Urethane* | METR-06 | S1110-U70 | | |
| MET-085TC | 1/2" BSPT | 1.36" | 0.97" | 4000 | | | METR-08 | S1112-U70 | | | |

*Optional seal materials are FKM (Viton), EPDM and Buna N - Example: MIT-045TCB = Buna N

TwistMate Internal Repair Kits

Swivel style repair kits contains 2 internal Buna N O-rings, 2 backup rings and 1 snap ring. Non-Swivel style repair kits contain 1 internal Buna N O-ring and 1 backup ring. Repair kits do not include main seal replacement.

For additional kits consult factory.



Need assistance finding a TwistMate connector for your application?

- Visit www.fastestinc.com and select "Connection Type" under "Products"
- Select a basic feature of your application such as "External Threads"
- Select TwistMate under Product Family or applications features such as "Connects to" to shorten your results list

| Application Calibration (49) Manufacturing (53) | | < <first 1="" 2="" 3="" 4="" 5="" <prev="" next=""> Last>></first> | | | | | |
|---|----------------|--|--|-----------------|--|--|--|
| Connection Type External Threads (69) | Q. m | MET-0210 Twist to connect for i swivel style, Urethan | nstant connection to 1/8" NP | T male threads. | | | |
| Connects To | Product Family | Connection Type | Connection M | ethod | | | |
| -10 (7/8-14) (2) -12 (1 1/18-12) (1) | TwistMate | External Threads | Twist to Connect Termination 1/8" NPT (Female) | | | | |
| -12 (1 1/16-14) (1) | Connects To | Pressure Rating | | | | | |
| -4 (7/16-20) (3) -6 (5/8-18) (1) -6 (9/16-18) (2) | 1/8" NPT | 5000 | | | | | |
| | | | | | | | |

Need operating or seal replacement instructions to extend connector service life?

- Find your connector above or use the part number search field in the website header, click "Learn More" button
- · Select the "Instructions" tab to display links to current instruction documents

| | | | MET-021021 Twist to connect for instant connection to 1/8* NPT male threads, swivel style, Urethane seals | | | | | |
|----------------------|--|-----------------------|---|------------------|----------------------------|--|--|--|
| | | | Product Family | Connection Type | Connection Method | | | |
| 600 | | | TwistMate | External Threads | Twist to Connect | | | |
| 0 | 2 | 1 | Connects To | Pressure Rating | Termination | | | |
| | and the state of | | 1/8" NPT | 5000 | 1/8" NPT (Female) | | | |
| | | | FIND A DEALER | ADD TO QUOTE | | | | |
| Overview | Specifications | Instructions | CAD Models | Related Products | | | | |
| external threads. Pr | nt below to view or download the oper use of the connectors will - Operating Instructions (MET) - Seal Replacement Instructions | ensure safe operation | | | onnectors from FasTest for | | | |



Connector Refurbishment Program



Extend the service life and warranty of your investment - Our connector refurbishment and competitor replacement program delivers the latest product improvements and ensures proper connector operation and performance in your application. Connectors routinely maintained can be refurbished or replaced economically relative to the cost of a new connector replacement.

Visit www.fastestinc.com or contact FasTest for details.

Warranty

Limited Express Warranty

FasTest Inc. warrants its products against defects in workmanship and materials for 12 months from the date of sale by FasTest Inc. or its authorized distributors. This warranty is void if the product is misused, tampered with or used in a manner that is contrary to FasTest Inc.'s written recommendations and/or instructions.

FasTest Inc. does not warrant the suitability of the product for any particular application. Determining product application suitability is solely the customer's responsibility. FasTest Inc. is not liable for consequential or other damages including, but not limited to, loss, damage, personal injury, or any other expense directly or indirectly arising from the use of or inability to use its products either separately or in combination with other products.

ALL OTHER WARRANTIES EXPRESS OR IMPLIED, WHETHER ORAL, WRITTEN OR IN ANY OTHER FORM, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

The sole and exclusive remedy under this warranty is limited to replacement of the product or an account credit in the amount of the original selling price, at the option of FasTest Inc. All allegedly defective products must be returned prepaid transportation to FasTest Inc., together with information describing the product's performance, unless disposition in the field is authorized in writing by FasTest Inc.

Notifications and Copyright

Notifications and Copyright

Specifications in this brochure are subject to change without notice. FasTest also reserves the right to make modifications and makes no guarantee of the accuracy of the information contained herein.

© 2012 FasTest Inc. All rights reserved. No part of this publication may be reproduced without written permission.



Calibration Connectors

The *FasCal* complete line of plug and play connectors for lab and field instrument calibration without the use of tapes, sealants and wrenches.



Medical Connectors

Versatile product line of connectors and systems for sealing and testing a wide variety of medical products and drug delivery devices.



Refrigeration Connections

The *CoreMax* system of high flow processing valves and connectors for the refrigeration manufacturing and service industry.



Compressed Gas Connectors

Innovative gas connectors for common CGA standards used in conventional and residual pressure valve filling applications.



1646 Terrace Drive • Roseville, MN 55113-1317 Phone: 651.645.6266 • Fax: 651.645.7390 Toll-free: 1.800.444.2373 www.fastestinc.com

美国FasTest中国区代理商:

深圳市慧烁机电有限公司 深圳市南山大道2019号 福临苑大厦16E (518052) 电话: 0755-8621 5125 / 5145 传真: 0755-8621 5195 邮箱:info@wisbay.cn 网站: www.wisbay.cn

上海办事处 上海市浦东新区新金桥路1088号 联创国际大厦1514室(201206) 电话: 021-6100 5201 / 5202 传真: 021-6100 5195

© 2012 FasTest Inc. All rights reserved.